

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B21C 23/14 // B60R 19/02	A1	(11) International Publication Number: WO 00/35610 (43) International Publication Date: 22 June 2000 (22.06.00)
(21) International Application Number: PCT/NO99/00375 (22) International Filing Date: 10 December 1999 (10.12.99) (30) Priority Data: 19985846 14 December 1998 (14.12.98) NO (71) Applicant (for all designated States except US): NORSK HYDRO ASA [NO/NO]; N-0240 Oslo (NO). (72) Inventor; and (75) Inventor/Applicant (for US only): VOLD, Rolf [NO/NO]; Rudslåtten, N-2830 Raufoss (NO). (74) Agent: RICANEK, Ivan; Norsk Hydro ASA, N-0240 Oslo (NO).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: METHOD OF MANUFACTURING STRUCTURAL MEMBERS (57) Abstract <p>A novel method of manufacturing structural members having closed cross-sectional configuration comprises steps of providing an open member (2) followed by reshaping/folding of its lateral parts and joining of abutted side walls into a co-extruded supporting longitudinally extending rib (21). The resulting structural member is preferentially a part of a vehicle body structure, e.g. a bumper beam.</p> <div data-bbox="812 1155 1412 1512">  </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

"Method of manufacturing structural members"

The present invention relates to a method of manufacturing longitudinal structural members having closed cross-sectional configuration, more particularly to manufacturing of bumper beams for vehicles and also to the members provided by such method.

Such longitudinal structural members, particularly the members made of Al or Al-alloys, are presently provided by extruding closed shapes having the required cross-sectional configuration and wall thickness in one operation.

However, provision of structural members like bumper beams for vehicles by simply extruding a double chamber closed shape is not offering a low cost, flexible manufacturing method ensuring simultaneously the lowest possible weight of the members. This is due to a number of disadvantages inherent to the extrusion process such as low extruding speed, increased die wear, limited choice of alloys and possibility for provision of thinner walls.

Furthermore, cross-sectional variations along the longitudinal extension of the members, often required due to limited available space or specific performance requests to structural members, are achieved by subsequent re-shaping/deformation of the cross-sectional configuration on pre-determined locations.

It is therefore an object of the present invention to provide a new method of manufacturing longitudinal structural members of closed cross-sectional configuration offering more freedom with regard to the functional configuration of the members and low material consumption.

A further object of the present invention is to provide a cheap manufacturing method and low weight structural members.

These and other objects are achieved in accordance with the present invention by provision of a novel manufacturing method and the resulting members as it appears from the attached patent claims 1 and 5.

Specific features and advantages of the present invention will be apparent from the following detailed descriptions of preferred embodiments of the structural beam with reference to the accompanying drawings, Figs. 1-5, where

- Fig. 1 is a schematical perspective view of an extruded open member,
- Fig. 2 illustrates schematically in a perspective view steps of reshaping and removing of excess material from the open member,
- Fig. 3 is a schematical perspective view of the reshaped member prior to the folding step of interim side walls,
- Figs. 4a,b show the formed closed shape member with abutted inwardly extending flanges ready for the final joining operation, and
- Figs. 5a,b illustrate schematically in a perspective and a vertical cross-sectional view, respectively, another embodiment of the member having a constant height along its longitudinal extension.

Referring to Figs. 1-4 illustrating by way of example the individual steps of manufacturing a bumper beam according to the present invention, only a half of the beam divided by a centre line OY-OY is shown in order to facilitate focusing on the preferred embodiment of the beam exhibiting variation in height and provision of a channel recession along the beam to protect the welded seam as a preferred type of joint.

Figure 1 shows in a schematical perspective view an open extruded member 2 comprising a base portion 21 provided with a rib 22 protruding longitudinally along the member.

Inherent advantages of extruding an open member compared to a closed shape configured member is a higher extruding speed, less wear of the extruding tool (die), larger choice of applicable alloys and possibility of weight-optimizing of the member by provision of thinner walls when and where appropriate.

Figure 2 illustrates schematically provision of lateral flanges 23,24 by means of any suitable method like e.g. pressing, rolling etc., followed optionally by gradual reduction of the flanges' lateral extension in the direction towards the end of the member by removal/cutting of material as depicted by the hatched fields.

Figure 3 illustrates an interim stage of the reshaping process from open to a closed shape configuration of the member 2 comprising provision of interim side walls 25,26 followed by a further reshaping step along the dotted lines, thereby folding the interim side walls 25,26 into a top portion 27 of a closed shape member by abutting the lateral flanges 23,24 on the top of the longitudinally extending rib 22 as shown in Figure 4a, followed by a joining/welding operation.

Figure 4b shows the formed closed shape member 3 in a preferred embodiment suitable for use as a bumper in vehicles exhibiting a channel-like recession 35 accommodating/-protecting a welding seam (joint) 36 joining the abutted flanges 23,24 and the rib 22, thereby providing two separate chambers 31,32.

Advantageously, thanks to the optional provision of flanges 23,24 exhibiting varying width, the channel recession 35 and thus the whole height H of the beam 3 is decreasing from the OY central line towards the end(s) as illustrated in a perspective view in Fig. 4a. This flexibility with regard to variation of cross-sectional area of the bumper beam is an important advantage resulting from the novel manufacturing method according to the present invention.

Customarily this effect is achieved by deforming (folding) of side walls of readily closed shape extruded members, thus increasing both the weight of the beam, the material consumption and thus the cost of the beams.

Although the present invention has been described and illustrated with respect to the preferred features and manner of manufacturing and preferred embodiments, it is to be understood that various changes and modifications may be made to the specifically described and illustrated arrangements without departing from the scope of the present invention.

Thus Figure 5 illustrates schematically in a perspective view and a cross-sectional view, respectively, a simplified embodiment of the structural member 3 exhibiting a constant height along its longitudinal extrusion. The interim side walls 25,26 from Figure 3 are in this case without provision of any lateral flanges directly folded into a top portion of the thereby provided closed shape member 3 being abutted and joined (welded) along the rib 22 providing two separate chambers 31,32.

Apart from the disclosed joining based on welding of the abutted walls of the member (preferentially friction stir welding), any other conventional joining techniques may be applied depending on the actual demand/performance to the structural member.

Consequently, structural members for different purposes having variation in the cross-sectional configuration, or constant cross-section with option for cutting of members having desired length, can be manufactured according to the present invention.

Claims

1. Method of manufacturing longitudinally extending structural members having a closed cross-sectional configuration comprising two or more chambers, said method comprising steps of
 - extruding an open member (2) having a base portion (21) provided with at least one longitudinally protruding rib (22),
 - reshaping of lateral parts of the member into a pair of interim side walls (25,26),
 - folding the interim side walls (25,26) into a top portion (27) of the thereby formed closed shape member (3) by bringing the folded abutted side walls to rest on the longitudinally extending rib (21), and finally
 - joining of the abutted side walls and the supporting rib(s) together by any suitable joining technique known per se.
2. Method according to claim 1,
c h a r a c t e r i z e d i n t h a t
the step of reshaping of the lateral parts of the open member (2) further comprises provision of lateral flanges (23,24).
3. Method according to claim 2,
c h a r a c t e r i z e d i n t h a t
excess material from the base portion (21) is cut prior to the reshaping step to provide inwardly extending flanges (23,24) exhibiting a varying height along the longitudinal extension of the folded closed shape member.
4. Method according to claim 1,
c h a r a c t e r i z e d i n t h a t
the joining of abutted walls is conducted by friction stir welding.

5. Structural member, particularly for application in a vehicle body structure comprising a hollow shape (3), where the cavity of the hollow shape is longitudinally divided into two or more chambers (31,32) by means of dividing rib(s) (22),
characterized in that
said rib(s) are integral co-extruded part(s) of open extruded member (2) providing a support for a joint (36) connecting the abutted walls of the folded member (2).
6. Structural member according to claim 5,
characterized in that
the hollow shape exhibits varying cross-sectional area along its longitudinal extension.
7. Structural member according to claim 5 or 6,
characterized in that
the joint (36) is a welded seam located in a channel-like recession (35) provided along said member's longitudinal extension by a pair of inwardly extending flanges (23,24).
8. Structural member according to one or more preceding claims,
characterized in that
the member is a bumper beam for vehicles.

1/2




Fig. 1




Fig. 2




Fig. 3




Fig. 4a




Fig. 4b




Fig. 5a




Fig. 5b

1
INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 99/00375

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B21C 23/14 // B60R 019/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B21C, B60R, B62D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9915365 A1 (NORSK HYDRO ASA), 1 April 1999 (01.04.99), figure 1 --	1-8
A	US 5540016 A (EDVIN L. CLAUSEN), 30 July 1996 (30.07.96), figure 1, abstract --	1-8
A	EP 0233552 A1 (METZELER KAUSCHUK GMBH), 26 August 1987 (26.08.87), figures 1,2 --	1-8
A	US 5085902 A (YUKIHIKO YADA ET AL), 4 February 1992 (04.02.92), abstract -----	1-8



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 March 2000

Date of mailing of the international search report

03-05-2000

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Katarina Ekman/MP
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/12/99

International application No.

PCT/NO 99/00375

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
WO	9915365	A1	01/04/99	AU 9284698 A	12/04/99
				NO 974375 A	23/03/99
US	5540016	A	30/07/96	AT 109411 T	15/08/94
				DE 69103257 D,T	23/03/95
				EP 0510060 A,B	28/10/92
				ES 2061231 T	01/12/94
				JP 5503053 T	27/05/93
				NO 900109 A	10/07/91
				WO 9110582 A	25/07/91
EP	0233552	A1	26/08/87	SE 0233552 T3	
				DE 8603371 U	12/06/86
US	5085902	A	04/02/92	DE 4011261 A	11/10/90
				GB 2231078 A,B	07/11/90
				JP 2267040 A	31/10/90